

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
TransOcean Oil, Inc.

3. ADDRESS OF OPERATOR
1700 First City East Bldg., Houston, Texas

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
77002
AT SURFACE: 790' FNL & 790' FEL of Sec. 31
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Vertical well.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Perforate	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 7760', PBTD 7660'

1-9-78 Drilled stage collar at 5784', clean out to 7660' PBTD, test to 4000#.

1-11 &


1-12-78 Spotted 250 gal. 15% MCA, perf. Dakota "B" 7514-23', frac w/1000 bbls. water & 40,000# sand. Set CI BP at 7482'. Test to 4000#. Perf. Dakota "A" 7400-42', frac w/1952 bbls. water and 80,000# sand.

1-21-78 Drilled CI BP at 7482'.

1-24-78 Ran 2-3/8" 4.7# J-55 tbg, landed at 7355'.

1-25-78 Well shut in. Hooking up tank battery.

Will test well next week.



Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Chief Prod. Clerk DATE 1-26-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

DURANGO OFFICE COPY