

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-28713

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Little Federal 20

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Chacon Dakota
Associated

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20-T24N-R3W
N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

Odessa Natural Corporation Attn: John Strojek

3. ADDRESS OF OPERATOR

P.O. Box 3908 Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790' FSL, 790' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6995' GL, 7008' DF, 7009' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/4/78 Spud Well

9/5/78 T.D. 370'
Ran 9 joints, 8-5/8", 24.0 lb., K-55 casing (348.60')
Set at 362.60' with 350 sacks Class "B" cement with 3%
Calcium Chloride and 1/4 lb. Flocele per sack. Cement
circulated. Pressure test with 500 psig. Test ok.

9/23/78 T.D. 7575'
Ran 176 joints, 4 1/2", 10.50 & 11.60 lb., K-55 casing (7551.53')
Set at 7561.43' with:

First Stage: 600 sacks 50-50 pozmix with 6 1/4 lbs. Gilsonite
and 6 lbs. salt per sack.

Second Stage: 150 sacks 65-35 pozmix (12% gel) with 6 1/4 lbs.
Gilsonite per sack. Followed by 50 sacks
Class "B" Neat Cement. State collar at 3264'.

FOR: Odessa Natural Corporation

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh, P.E.

President, Walsh Engineering
& Production Corp.

DATE 9/26/78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

SEP 28 1978

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.