Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

PORM APPROVED					
Budget Bureau No. 1004-0135					
Expires: March 31, 1993					

DISTRICT MANAGER

•	Lease	Designation	and	Serial
	NM	33039		

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
--------	---------	-----	---------	----	-------

6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different/reservoir. Use "APPLICATION FOR PERMIT—" for such proposals! 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Well P&A 8. Well Name and No. 2. Name of Operator Raspberry 1 Dugan Production Corp. 9. API Well No. 3. Address and Telephone No. 30-039-21816 P.O. Box 420, Farmington, NM 87499 10. Field and Pool, or Exploratory Area (505) 325-1821 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Escrito Gallup 11. County or Parish, State 790' FSL - 790' FWL 11/ Sec. 26, T24N, R7W, NMPM Rio Arriba, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Conversion to Injection Altering Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Plugged well as follows: Set cast iron bridge plug a 54801. Spot 9 cu. ft. class 8 cement on top of cast iron bridge plug. Gallup plug 5380 Spot 14 cu. ft. class B cement at 3725'. Hesa Verde plug from 3725 to 3575'. 2. 3. Spot 30 cu. ft. class B cement plug at 2230'. Pictured Cliffs - Fruitland plug from 2230' - 1900'. Spot 33 cu. ft. class B cement at 1775'. Ojo Alamo plug 1775 to 1400'. Perforate 4%" casing 2 3041. Cement to surface with 166 cu. ft. class 8 with 4% get cement - leaving 4%" casing and 4% - 8-5/8" annulus full of cement. Job complete 10-26-93. Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

14. I hereby certify that the forgoing if true and correct  Signed John Cliff Wells  Trian Appearation	Title	Operations Manager	Date _	10/28/93
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Title		Date 1	PROVED
	···		1	100 0 3 1993
Fide 18 U.S.C. Section 1001, makes it a crime for any person kn or representations as to any matter within its jurisdiction.	owingly and willfu	lly to make to any department or agency of the Unite	ed States any Miles.	ficitions or fraudulent statements

\*See Instruction on Reverse Side

