

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR
Mobil Oil Corporation3. ADDRESS OF OPERATOR
9 Greenway Pl., Ste 2700, Hou., TX 770464. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 890 FSL & 990 FWL
AT TOP PROD. INTERVAL: Same as surface
AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Spud & set 8-5/8 @ 339
5-1/2 @ 68945. LEASE
Jicarilla Contract #12

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla Otero Com.9. WELL NO.
110. FIELD OR WILDCAT NAME
Basin Dakota11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 22, T24N, R5W12. COUNTY OR PARISH
Rio Arriba13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6677 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded: 9:30 PM 5/4/79. Ran 8 jts 8-5/8, 24#, K55 set @ 339 Dowell cmt. w/ 225 sx A + 290 + 1/4 #FC, PD 6:45AM 5/5/79 cmt. circ. 6900 TD, prep log, sd. & sh., 7-7/8 hole, TD 10PM 5/18/79. Set 5-1/2 csg @ 6894, Dowell cmt. in 3 stages w/ 865 sx. cmt. did not circ. NU relrig 2 AM 5/23/79. MIRU Flint DD Ut. 5/24/79 cmt @ 970, att to drill out around 8-5/8, found csg. split, back off csg. @ 10' below gl. Welded on new 10' sect pumped 360 sx. cmt. DO cmt 2280 -2383, PI 2-1/2 BPM @ 1000, hole in csg @ 2375, prep to sqz. Dowell pumped 200 sx @ 1500 psi @ 2 BPM/ISIP700, over displ. 5 bbls.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Robbie Jay TITLE Authorized Agent DATE 6/4/79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

