

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1450' FSL x 1190' FEL, Section 5,
AT SURFACE: T25N, R5W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud & Set Casing	

5. LEASE
Jicarilla Contract 147

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache Tribal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla Contract 147

9. WELL NO.
2E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NE/4 SE/4 Section 5, T25N, R5W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
NM

14. API NO.
30-039-22085

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6673' GE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 8/5/79. Drilled to 308' and set 8-5/8" casing with 325 sx Class "B" Neat, 2% CaCl₂ cement. Circulated out 20 sx good cement.

Drilled 7-7/8" hole to 7500' & set 4-1/2", 11.6# casing at 7546'. Cemented with 520 sx, Class "B", 50:50 Poz with 6% gel, 2# medium tuf plug per sx, 0.8% fluid loss additive. Tailed in with 100 sx Class "B" Neat cement. Circulated out 4 sx good cement.

Cemented second stage with 975 sx Class "B" Dowell Lite Poz (50:50) with 6% gel, 2# medium tuf plug per sx and 0.8% fluid loss additive. Tailed in with 100 sx Class "B" Neat cement. Circulated out 20 sx good cement.

Released rig on 8/23/79.
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed By _____
SIGNED E. E. SVOBODA TITLE Dist. Adm. Supvr. DATE 8/30/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

