

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR

Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 3280, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2326' FNL & 1840' FWL (SE NW)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Well History

5. LEASE

Jicarilla 35

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla

9. WELL NO.

7

10. FIELD OR WILDCAT NAME

Otero - Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 1-24N-50

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. Elev. 6773'; K.B. 6786'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to 6,620' & ran logs.

Ran 171 jts 4 1/2" O.D., 10.5#, K-55, R-3, LT&C, New casing set @ 6619' (K.B.) w/ stage tool set @ 3949'. Cmt'd 1st stage w/275 sx Class "B" cmt w/0.6% Halide 9 predeeded w/36 bbl of Spacer 1000. Opened stage collar + circulated 4 hr. Cmt'd 2nd stage w/150 sx of 65-35 pozmix w/12% gel, followed w/575 sx of 50-50 Pozmix w/2% gel + 1/4# Flocele/sx. Predeeded w/36 bbl of spacer. Closed stage collar + pressure tested to 2000 PSI. Good circ throughout both jobs. Plug down 12:25 p.m., 9-3-79.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE Drlg. Supt.

DATE

9-4-79

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE

SEP 10 1979

CONDITIONS OF APPROVAL, IF ANY:

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.