UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Jicarilla 35 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SORVET	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different	
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	Jicarilla
Well was a second and a second	9. WELL NO.
2. NAME OF OPERATOR Energy Reserves Group, Inc.	10 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Otero Gallup
P.O. Box 3280 Casper, Wyoming 82602	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA AREA AREA
below.) 1261' FNL & 1840' FWL	Section 2, T24N-R5W 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 1201 TNE & 1040 TNE AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH: (NE/NW)	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	G.L. Elevation 6779', K.B. 6792'
TEST WATER SHUT-OFF	기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기
FRACTURE TREAT	등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등
SHOOT OR ACIDIZE	그 그 사람들은 사람들이 되었다.
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent.	irectionally drilled, give subsurface locations and
The above described well was spudded @ 10:00	P.M., 8/1/79.4
Drilled 12½" hole to 527' (K.B.).	
printed in the contract of the	그는 그는 그를 가장 하는 그를 가장 있었다.
Ran 13 jts 505.16' (Net) - 8 5/8" O.D., 24	4#, k-55, 8Rth, S.T.& C.
New casing set @ 518' (K.B.). Cemented w/325	sx. of Class "B" cement w/2%
CaCl ₂ & ¼# Flocele/sx. Plug down @ 2:45 P.M.	, 8/2/79. Good cement returns.
Nippled up and pressure tested BOPE to 800 ps	i for 30 minutes - Held O.K
Drilled out w/7 7/8" bit after 12 hours.	SI. 101 30 REIRIUES REIL
Difficu out w// //b Dit ditel 12 hours.	
and Type	Set @ Ft.
Subsurface Safety Valve: Manu. and Type	TOIL CON COM.
18. I hereby certify that the foregoing is true and correct	DIST. 3
SIGNED POSCOE Chilespee TITLE Drilling Suj	ot. DATE August 3, 1979
SIGNED FOR COLLEGE SUPER TITLE Drilling Sup Ay Wear Former (This space for Federal or State of	fice use)
3 /	DATE
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	AUG - 6 1979
	ALL MULLINGS

U. S. GEOLOGICAL SURVEY