Form Approved.

1973 Budget Bureau No. 42-R1424 **UNITED STATES** 5. LEASE DEPARTMENT OF THE INTERIOR Jicarilla 35 **GEOLOGICAL SURVEY** 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache 🦠 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME Jicarilla : 1. oil gas well \square **KX** well other 9. WELL NO. 😤 கீ 🥸 🚉 2. NAME OF OPERATOR Energy Reserves Group, Inc. 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR Basin-Dakota P.O. Box 3280 Casper, Wyoming 82602 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: 1,750' FSL & 840' FEL (NE/SE) 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: Rio Arriba New Mexico AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) G.L.- 6,921!;K.B. 6,935! REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: Allogot be stable to a reignor TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone Report results or many change on Form 9–330.) PULL OR ALTER CASING MULTIPLE COMPLETE 누천선병 High and selection of the selection of t CHANGE ZONES ABANDON* (other) Well History 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If wen is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled 7-7/8" hole to 7,517'(KB) and ran logs Ran 183 jts $4\frac{1}{2}$ " OD, 11.6# & 10.5#,K-55, R3,8rth, ST&C, New Casing Set @ 7517'KB w/stage collar @ 5546' KB Cemented 1st stage w/540 sx. 50-50 Pozmix & cement w/2% Gel Good circ. throughout job. Openend stage collar and circulated six hours between stages. Cemented 2nd stage w/870 sx 65-35 pozmix and cement w/6% Gel & 岩# Flocele/sk. followed by 100sx Class "B" cement w/岩# Flocele/sx plug down at 7:00P.M. 2-8-80 Good cement returns 2-11-80 W.O.C. & W.O.C.T. Subsurface Safety Valve: Manu. and Type _ 18. I hereby certify that the foregoing is true and correct _ TITLEDrilling Foreman DATE (This space for Federal or State office use)

FEB 1 4 '80

APPROVED BY

-

*See Instructions on Reverse Side

TITLE

U. S. GEOLOGICAL SURVEY DURANGO, COLO.

DISTRICT

ACCEPTED TORORETORNAL, IF ANY: