

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,750' FSL, 840' FEL (NE SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
APR 17 1989U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Perf Dakota 7,378'-82'; 7,392'; 7,406'-08'; 7,420'-28' w/1 JSPF (18 holes).
B.D. w/1500 Gals Smith 7-1/2% HAS-1 acid + additives + 10% Methanol + 500
SCF N₂/bbl. + 30 Ball Sealers. Fraced w/65,000 Gals 30# GWX-4 Gel + 10%
Methanol + 2% Diesel + 500 SCF N₂/bbl + 120,000# 20-40 Sand.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Hean B. Barnes

TITLE

Dist Prod Engr-RMD

DATE

APR 11 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

