

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Petro-Lewis Corporation  
3. ADDRESS OF OPERATOR  
P.O. Box 937 Levelland, Texas 79336  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2170' FNL & 1000' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) set 4 1/2" OD casing at TD

5. LEASE  
SF-080566  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Federal  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Ruddock  
9. WELL NO.  
7  
10. FIELD OR WILDCAT NAME  
Blanco Mesaverde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3, T25N, R3W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7337' Gr

EIVE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

NOV 05 1979

OFFICIAL SIGNATURE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

0-26-79 Drilled 7 7/8" OD hole to 6320'.  
Ran Compensated Neutron and Dual Induction-SFL logs.  
Ran 144 joints 4 1/2" OD 10.5# K-55 STC casing to 6300' RKB.  
Cemented 1st stage with 275 sacks Lite cement with 1/4# flocele per sack followed by 200 sacks class "A" cement with 1/4# flocele per sack. Circulated 5 barrels cement to surface.  
Cemented 2nd stage with 400 sacks Lite cement with 1/4# flocele per sack followed by 150 sacks class "A" cement with 2% calcium chloride and 1/4# flocele per sack.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED George Amron TITLE Production Accountant DATE 10/31/79

(This space for Federal or State office use)

APPROVED BY TITLE DATE  
CONDITIONS OF APPROVAL, IF ANY:

## Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1975 O - 214-140