

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Petro-Lewis Corporation

3. ADDRESS OF OPERATOR

P.O. Box 937 Levelland, Texas 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2130' FNL & 960' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud & set 8 5/8" casing

5. LEASE  
SF-080566

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Federal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Florance

9. WELL NO.  
7-A

10. FIELD OR WILDCAT NAME  
Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 4 T25N R3W

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7264' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded well 9-18-79 at 3 p.m.

2. Drilled 12 1/4" OD hole to 520'.

3. Ran 12 joints 8 5/8" OD 24# K-55 STD casing set at 510.90 RKB. Cemented with 150 sacks class "A" cement with 4% gel, 2% Calc. Chl. and 1/4# Flocele per sack; followed by 200 sacks class "A" cement with 2% Calc. Chl. and 1/4# Flocele per sack. Cement circulated to surface.

4. Pressure tested 8 5/8" OD casing to 300# for 30 minutes.

5. Drilled out cement & resumed drilling 7 7/8" OD hole.

Subsurface Safety Valve: Manu. and Type

Set @ DIST. 3 Ft

18. I hereby certify that the foregoing is true and correct

SIGNED George Dameron TITLE Production Accountant DATE September 21, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

SEP 24 1979