

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1850' FEL x 1850' FSL, Section 13,
AT SURFACE: T25N, R4W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Spud and Set Casing</u>	

5. LEASE
Jicarilla Contract 124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla Apache Tribal 124

9. WELL NO.
3

10. FIELD OR WILDCAT NAME
Ojito Gallup-Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/4 SE/4 Section 13,
T25N, R4W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
NM

14. API NO.
30-039-22140

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7088' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole on 9/6/79. Drilled to 312' and 8-5/8", 24# surface casing at 309'.

Cemented casing with 315 sx Class "B" cement containing 2% CaCl₂. Circulated out 20 sx good cement to surface.

Presently drilling 7-7/8" hole to TD.

Subsurface Safety Valve: Manu. and Type _____ Set _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Adm. Supvr. DATE 9/18/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



SEP 20 1979
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.