

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1850' FEL x 1850' FSL, Section 13,

AT TOP PROD. INTERVAL: Same

T25N, R4W

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Completion Procedure

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

Jicarilla Contract 124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache Tribal 124

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Ojito Gallup-Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

NW/4 SE/4 Section 13, T25N, R4W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

New Mexico

14. API NO.

30-039-22140

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7088' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 10-26-79. Cleaned out hole to plug back depth of 8170'. Total depth is 8220'.

Perforated first stage from 7932' to 7944' with 2 spf, total of 24 holes. Sand water fraced with 48,384 gallons of frac fluid and 90,720# of sand.

Perforated second stage from 7777' to 7858' with 2 spf, total of 22 holes. Sand water fraced with 32,886 gallons of frac fluid and 71,022# of sand.

Perforated third stage from 7034' to 7170' with 2 spf, total of 170 holes. Sand water fraced with 91,658 gallons of frac fluid and 201,700# of sand.

(over)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Adm. Supr. DATE

(This space for Federal or State office use)


APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



U. S. GEOLOGICAL SURVEY
DURANGO, COLO.