

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0115
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other	5. Lease Designation and Serial No. NM 23024
2. Name of Operator Dugan Production Corp.	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. P.O. Box 420, Farmington, NM 87499 (505) 325-1821	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1780' FSL & 1670' FWL Sec. 6, T24N, R1W	8. Well Name and No. Eureka #1
	9. API Well No. 30-039-22166
	10. Field and Pool, or Exploratory Area Undes. Nacimiento
	11. County or Parish, State Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☒ Notice of Intent	☐ Abandonment
☐ Subsequent Report	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other Amend Plug Procedure
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Amend plugging procedure as follows:

1. Set 2-7/8" cast iron bridge plug at 3450' (Pictured Cliffs top at 3500' with top perforation at 3503').
2. Run 1 1/2" tubing and spot Class B cement to 3050' on top of plug to cover Fruitland top at 3370' and Ojo Alamo top at 3100'.
3. Set cast iron bridge plug at 2390' (Nacimiento top and top perforation at 2438'). Spot Class B cement through tubing on top of plug to 2340'.
4. Perforate at 185' (surface casing set at 134') and cement to surface for surface plug.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander Title Operations Manager Date 8/8/95
(This space for Federal or State office use)
Approved by Robert Kent Title Chief, Lands and Mineral Resources Date AUG 15 1995
Conditions of approval, if any: