

5-USGS (Durango) 1-File

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Dugan Production Corp.
3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
880' FSL - 1800' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

5. LEASE
NM 23027
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Almage
9. WELL NO.
1R
10. FIELD OR WILDCAT NAME
South Blanco PC
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 27 T24N R1W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7378' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-19-79
Went in hole w/drill pipe. Laid down drill pipe and drill collars. Ran 108 jts 2-7/8" 6.4# CW-55 10R reg tbg for csg. TE 3142.88' set @ 3142' GL. Preflushed hole w/5 bbls mud flush. Cemented w/75 sx 65-35 w/12% gel w/1/4# flocele per sx followed by 50 sx class "B" neat w/1/4# flocele per sx. Total slurry 256 cu ft. Estimated cement top 550'. Reciprocated pipe and had good circulation while cementing. Bump ed plug w/2000 psi. Released to 800 psi. Shut in POB 12:45 a.m. 12-19-79

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas A. Dugan TITLE Petro. Eng. DATE 12-19-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

DEC 21 1979

GEOLOGICAL SURVEY