

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
SF-078563

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Grace Petroleum Corporation		8. FARM OR LEASE NAME Grace Federal 24	
3. ADDRESS OF OPERATOR 1515 Arapahoe St., Denver, Colorado 80202		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 950' FNL, 1640 FWL		10. FIELD AND POOL, OR WILDCAT Escrito	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 24. T24N 7W	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6644' GL		12. COUNTY OR PARISH Rio Arriba	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling of said well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-13-80 Spud 12½" surface hole drill to 340' run 330' 8 5/8" csg
3-14-80 Drill 7-7/8" hole to 1850
3-15-80 Drill 7-7/8" hole to 3050
3-16-80 Drill 7-7/8" hole to 3572
3-17-80 Drill 7-7/8" hole to 4215
3-18-80 Drill 7-7/8" hole to 4735
3-29-80 Drill 7-7/8" hole to 5262
3-20-80 Drill 7-7/8" hole to 5650
3-21-80 Drill 7-7/8" hole to 5700 T.D.
3-22-80 Attempt to LOE. Logs would not go. Trip in hole to knock off bridges
3-23-80 Run dual induction log, Formation density, and compensated neutron log.
3-24-80 Ran 144 jts 4½" 10.5# K-55 57C csg. csg. shoe @ 5717, Float 5677', DV tool
300Y. 1st. stage 275 sx 65-35 pozmix w/2% Gel, 6# Ksx Gilsonite, & 10% salt.
2nd. stage 300 sx 65-35 pozmix w/12 % Gel & 6#/sx Gilsonite Tailed in
100 sx 50-50 poz w/2% Gel.

RECEIVED
JUN 11 1980
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED Barry Stronhey TITLE Operations Engineer DATE May 27, 1980

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED FOR _____
DATE _____

JUN 18 1980

*See Instructions on Reverse Side

FARMINGTON, N. M.
JUN 18 1980