

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
501 Airport Dr., Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1820' FSL x 1695' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.
REPORT OR OTHER DATA

REQUEST FOR APPROVAL TO

TEST WATER SHUT OFF

FRACTURE TREAT

SHOOT OR REGRAB

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON

(other) Recompletion ☒

SUBSEQUENT REPORT OF:

RECEIVED

MAR 16 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or change on Form 9-330.)

17. ON PLUG BACK OPERATIONS, REPORT ON PLUG BACK. (Clearly state all pertinent data, including pertinent well logs, estimated rate of flow, and measured work. If well is directionally drilled, give subsurface location, measured and true vertical depth, for all markers and zones pertinent to this work.)

Recompletion operation commenced 12-7-82. Total depth of the well is 7048' and plugback depth is 6948'. Perforated intervals 5972-5952', 5952-5916', 5848-5808', and 5796-5758' with one .38" jsf for a total of 134 holes. Fraced interval 5972-5758 with 121,333 gals. of 70% quality foam containing 20# gelled water, 2% KCL, 2570 scf of nitrogen and 207,500# of 20-40 mesh sand. Landed 2-3/8" tubing at 6940' and released rig on 12-14-82. Gallup is producing through a sliding sleeve.

RECEIVED

APPROVED BY: [Signature] SPECIAL AGENT IN CHARGE
CONDITIONS OF APPROVAL, IF ANY

DATE

MAR 18 1983

FILED

*See Instructions on Reverse Side

NMOCC