

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1520' FNL x 1030' FWL, Section 9,

AT TOP PROD. INTERVAL: Same T25N, R5W

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other) Set Production Casing

SUBSEQUENT REPORT OF:

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7-7/8" hole to TD of 7546'. Set 4-1/2", 11.60# casing at 7546' on 11/14/79. Set DV tool at 5393' and cemented casing in 2 stages:

- 1) 375 sx class "B" Neat cement containing 50:50 Poz, 6% gel, .8% fluid loss additive, 2# Medium tuf plug per sx. Tailed in with 175 sx class "B" Neat cement. Circulated out 20 sx Good cement.
- 2) Cemented with 1115 sx class "B" Light cement containing 50:50 Poz, 6% gel, .8% fluid loss additive, and 2# Medium tuf plug per sx. Tailed in with 100 sx class "B" Neat cement.

Released rig on 11-14-79.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE Dist. Adm. Supr.

DATE 11-29-79

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NOV 30 1979

U. S. GEOLOGICAL SURVEY
FEDERAL GOVT.