

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
KENAI OIL AND GAS INC.

3. ADDRESS OF OPERATOR  
717 17th Street, Ste. 2000, Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 705' FNL - 790' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| REQUEST FOR APPROVAL TO:                      | Subsequent Report of:    |
|---|--------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/> |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/> |
| ABANDON* <input type="checkbox"/>             | <input type="checkbox"/> |

(other) Status: Drilling or Completing

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/7/80: TD 3620'. Waiting on completion rig. Ran I-ES logs 3620-213' and G/R Density-Neutron 3620-1525'. Rig up and ran 84 jts., 4-1/2" OD, 10.5#, K55-8RT-STC-R3 new casing w/guide shoe, float collar and 4 centralizers, 3621.96'; and landed at 3620' GL. Cemented w/75 sxs. 65-35 Pozmix w/12% gel and 1/4# Cello-Flake per sx; followed by 150 sx. Class B cement w/12-1/2# Gilsonite and 1/4# Cello-Flake per sx. Preceded cement w/10# Mud-Flush. Full circulation while cementing. Bumped plug w/1200 psi, released pressure and float held o.k. at 12:40 p.m., 2/6/80. Set slips and released rig at 1:10 p.m., 2/6/80.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct  
SIGNED George O. Judd TITLE Manager-Drilling and Production DATE 2/8/80

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

FEB 11 80

DISTRICT

\*See Instructions on Reverse Side

5. LEASE  
NM-23026

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
NONE

7. UNIT AGREEMENT NAME  
NONE

8. FARM OR LEASE NAME  
FEDERAL 18

9. WELL NO.  
#11 ~~18~~

10. FIELD OR WILDCAT NAME  
Gavilan PC - So. Blanco Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T24N-R1W

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7437' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

