Name DISTRICT,

## UNITED STATES DEPARTMENT OF THE INTERIOR

|  | DEPARTMENT OF THE INTERIOR  | NM-23033   |
|--|---|--|
| GEOLOGICAL SURVEY  |   | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE  |
| SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)  1. oil gas KY |   | I NUME   |
|  |   | 8. FARM OR LEASE NAME<br>FEDERAL _3  |
| well   | gas well other  | 9. WELL NO.  |
|  | OIL AND GAS INC.  | #31-3-<br>10. FIELD OR WILDCAT NAME  |
|  | s of operator<br>7th Street, Ste. 2000, Denver, CO 802  | Undesignated 202 11. SEC., T., R., M., OR BLK. AND SURVEY C  |
|  | N OF WELL (REPORT LOCATION CLEARLY. See space   | AREA Soc 2 T24N D2M  |
| below.)<br>AT SURF   | FACE: 790' FNL & 1850' FEL  | Sec. 3, T24N-R2W  12. COUNTY OR PARISH 13. STATE   |
|  | PROD. INTERVAL:   | Rio Arriba New Mexico  |
| AT TOTA  | AL DEPTH:   | 14. API NO.  |
|  | APPROPRIATE BOX TO INDICATE NATURE OF NOTI  |  |
| REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  |   | 15. ELEVATIONS (SHOW DF, KDB, AND WE 7235 GR; 7243' KB   |
| MULTIPLE C<br>CHANGE ZOI<br>ABANDON*   | NES 🗍   |  |
|  | tus of drilling or completion   | state all portinent details, and give portinent date   |
| 17. DESCRIE  | Etus of drilling or completion  BE PROPOSED OR COMPLETED OPERATIONS (Clearly gestimated date of starting any proposed work. If well and true vertical depths for all markers and zones per  | l is directionally drilled, give subsurface locations an   |
| 17. DESCRIE including measure  | BE PROPOSED OR COMPLETED OPERATIONS (Clearly gestimated date of starting any proposed work. If well   | Tis directionally drilled, give subsurface locations are rinent to this work.)*  TD 3414' KB & ran GO International (2"0D, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Eumped 110 w/1000   |
| 17. DESCRIE including measure  | BE PROPOSED OR COMPLETED OPERATIONS (Clearly gestimated date of starting any proposed work. If well and true vertical depths for all markers and zones per Moving out rotary rig. Drilled to logs. Ran 82 jts., (3446.31') 4-1/ and landed @ 3416' KB and cemented gel and 10% salt. Full returns whi @ 9:30 a.m., 1/17/80. Set casing s                              | TD 3414' KB & ran GO International 2"OD, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Bumped plus w/1000 lips and cut off casing JAN241980 CIL CON. COM. DIST. 3  |
| 17. DESCRIE including measure  1/18/80:  | BE PROPOSED OR COMPLETED OPERATIONS (Clearly gestimated date of starting any proposed work. If well and true vertical depths for all markers and zones per Moving out rotary rig. Drilled to logs. Ran 82 jts., (3446.31') 4-1/ and landed @ 3416' KB and cemented gel and 10% salt. Full returns whi @ 9:30 a.m., 1/17/80. Set casing s released @ 12 noon, 1/17/80. | TD 3414' KB & ran GO International (2"0D, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Bumped 1999 w/1000 slips and cut officasing (CIL CON. COM. DIST. 3   |
| 17. DESCRIE including measure  1/18/80:  | BE PROPOSED OR COMPLETED OPERATIONS (Clearly gestimated date of starting any proposed work. If well and true vertical depths for all markers and zones per Moving out rotary rig. Drilled to logs. Ran 82 jts., (3446.31') 4-1/ and landed @ 3416' KB and cemented gel and 10% salt. Full returns whi @ 9:30 a.m., 1/17/80. Set casing s released @ 12 noon, 1/17/80. | TD 3414' KB & ran GO International 2"OD, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Bumped plus w/1000 lips and cut off casing JAN241980 CIL CON. COM. DIST. 3  |
| 17. DESCRIE including measure  1/18/80:  Subsurface S  18. I hereby  | Moving out rotary rig. Drilled to logs. Ran 82 jts., (3446.31') 4-1/ and landed @ 3416' KB and cemented gel and 10% salt. Full returns whi @ 9:30 a.m., 1/17/80. Set casing s released @ 12 noon, 1/17/80.  | TD 3414' KB & ran GO International 12"0D, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Bumped 11 w/1000 lelips and cut off casing W/1000 |
| 17. DESCRIE including measure  1/18/80:  Subsurface S  18. I hereby  SIGNED APPROVED BY  | Moving out rotary rig. Drilled to logs. Ran 82 jts., (3446.31') 4-1/and landed @ 3416' KB and cemented gel and 10% salt. Full returns whi @ 9:30 a.m., 1/17/80. Set casing s released @ 12 noon, 1/17/80.  Safety Valve: Manu. and Type  Certify that the foregoing is true and correct  Manager-Drilli  TITLE  (This space for Federal or Sta                        | TD 3414' KB & ran GO International 12"0D, 10.5#, J-8RT-R3 new casing w/250 sxs., 50-50 Pozmix plus 2% le cementing. Bumped 11 w/1000 lelips and cut off casing W/1000 |

,attel \*See Instructions on Reverse Side