

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 23039

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 29

9. WELL NO.

34-29

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 29,
T 25N-R 2W

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

1. OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

KENAI OIL AND GAS INC.

3. ADDRESS OF OPERATOR

2000 Energy Center One/717-17th Street, Denver, CO. 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990 FSL, 1650 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7107 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Status of Dring. or Compl.

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING


ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-22-79: MIRU Corrosion Control Rig #1 from Federal 31-3. Drill pilot hole, 6 1/4", to 220' GL.

12-23-79: Reamed 6 1/4" pilot hole to 8-3/4", then 12 1/4" to 220'. RU and ran 5 joints 8-5/8"-23# - J - 8RT - R3 new casing with guide shoe and insert float. Landed casing at 213' GL and cemented with 200 sx Class B cement with 3% CaCl and 1/4# Flo-Seal per sx. Full returns while cementing. Circulated 12 bbls. slurry. Plug down at 7:00 PM and shut down for holiday.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Manager-Drilling & Production DATE 12-26-79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

G. GEOLOGICAL SURVEY
DURANGO, COLO.