

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Jerome P. McHugh
3. ADDRESS OF OPERATOR  
Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FSL - 1650' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM 23039
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal 29
9. WELL NO.  
34-29
10. FIELD OR WILDCAT NAME  
Undesignated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 29 T25N R2W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7107' GL

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- |                      |                          |                          |
|----------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT       | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE    | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES         | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* csg         | <input type="checkbox"/> | <input type="checkbox"/> |
| (other)              | <input type="checkbox"/> | <input type="checkbox"/> |

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-15-80  
Ran 83 jts 4-1/2" OD 10.5# J-55 8R csg. TE 3505.40' set @ 3480' RKB.  
Circulated and washed down 7' to TD Cemented w/75 sx 65-35 w/12% gel  
w/1/4# cello flake per sx followed by 125 sx class "B" w/12.5# gilsonite per  
sx. Total slurry 372 cu ft. Had good circulation and reciprocated pipe  
while cementing. Bumped plug w/1600 psi. Held OK. POB 11:50 a.m.  
Set slips and rig released at 12:00 noon 3-15-80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Agent DATE 5-9-80  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAY 13 1980  
CONDITIONS OF APPROVAL, IF ANY:

NMCCG

BY M. L. Kuchera