

1 - File  
Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Dry Hole

2. NAME OF OPERATOR  
Jerome P. McHugh

3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL - 1650' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>
(other) _____	

SUBSEQUENT REPORT OF:

REPORT OF:  
RECEIVED

JUL 9 1961

(NOTE: Report results of multiple completed change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

RECEIVED

JUL 13 1981

OIL CON. COM.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to plug and abandon this well in the following manner:

1. Squeeze perfs w/ 20 sx cement and leave cement plug in 4½" csg. 3426-3342'
2. Spot cement plug 3290-3190'
3. Spot cement plug 3154-3254'
4. Find free point and shoot off 4½" csg.
5. Spot plug 50' inside and 50' top of stud
6. Spot 100' plug, base of surface csg.
7. Spot 50' plug, top of surface csg.
8. Install dry hole marker and restore location.

NOTE: Verbal approval obtained 7-7-81 from Richard Bell.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Agent DATE 7-8-81

(This space for Federal or State office use)

**REPORT FOR RECORD**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

JUL 09 1981

NMOCC

• See Instructions on Reverse Side

BY Dean Elliott