

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ Dry hole ☐

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

below.)
AT SURFACE: 990' FSL - 1650' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF:

RECEIVED (NOTE: B)

OCT 09 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Squeezed perfs 3426-3342' with 20 sx cement.
2. Spotted 28 sx cement plug 3426-3057'.
3. Found free point and shot 4½" csg. off at 1022'.
4. Spotted cement plug 50' inside 4½" csg. and 50' above csg. stub 1072-972'.
5. Spotted 100' stub in base of surface csg. 263-163'.
6. Placed 50' plug and installed dry hole in top of surface csg.
7. Filled pits and restored location.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 10/1/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

MMOC
Instructions on Reverse Side

Set @ _____ Ft.

OIL CON. DIV
DIST. 3

4-8-81

APPROVED
AS AMENDED

DEC 11 1984
J. Stan. McKee

M. MILLENBACH
AREA MANAGER