

Form 7500
(May 1903)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Submit in triplicate
(Other instructions on re-
verse side)

Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078532

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
Grace Petroleum Corporation

3. ADDRESS OF OPERATOR
Ste. 200, 3 Park Central, 1515 Arapahoe, Denver, Colo. 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
960' FSL, 960' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether LF, RT, GR, etc.)
6911 GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mesa A

9. WELL NO.
3

10. FIELD AND POOL, OR WILDCAT
Escrito

11. SEC., T., R., H., OR BLK. AND
SURVEY OR AREA
Sec. 25, T24N-R7W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling of said well

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/24/80 Spud w/12 1/4" Bit @ 8:30 P.M.

3/25/80 Drilled 320' 12-1/4" hole set 8-5/8 24# csg.to 310' w/225 sx cmt & 2% CaCl.

3/26/80 Depth 1702

3/27/80 Depth 2960

3/28/80 Depth 3630

3/29/80 Depth 4405

3/30/80 Depth 4894

3/31/80 Depth 5422

4/1/80 Depth 5748 TD

4/2/80 Ran induction electrolog, compensated densilog, compensated neutorn, and gamma ray

4/3/80 Ran 144 Jts. 4 1/2" 10.5 # Stc K-55 csg to 5748 Td. Shoe depth 5748, Float 5708, Dv tool 3103'. 1st. stage cmt w/250 sx 50-50 pozmix. 2nd. stage 65-35 pozmix w/6% Gel, 6 1/2 #/sx Gilsonite Tailed w/ 50 sx class 'G' containing 2% CaCl.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Operations Engineer

DATE May 27, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 18 1980

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY