

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
CONTRACT 124

6. If Indian, Allottee or Tribe Name
JICARILLA APACH

7. If Unit or CA, Agreement Designation

8. Well Name and No.
JIC.APACHE TRIB

9. API Well No.
124#5

10. Field and Pool, or Exploratory Area
LIND. GL/DK W.

11. County or Parish, State
RIO ARriba, N.M.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
MW PETROLEUM CORPORATION

3. Address and Telephone No.
304 N. BEHREND, FARMINGTON, N.M. (505) 325-0318

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1670 FNL X 955 FEL, S-23 T-25N, R-4W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other **Temporary Abandonment**

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

As per Sundry Notice of Intent approved 7-21-92 per verbal - Wayne Townsend.

7-10-92, set CIBP @ 6715'. Spot 25 sx (29.5ft3) class B neat cement f/6494' to 6715'. Squeeze 100 sx (118ft3) class B cement into bad casing interval f/3316' to 344'.

7-13,14-92 Drill out cement, squeeze broke down @ 600 psi press test.

7-15-92 Resqueeze same interval w/50sz (59ft3) class B cement.

7-16,17-92 Drill out cement, press test csg f/surface to 6494' to 600 psi - press held.

7-20-92 Circulate well w/150 bbls water containing 55 gal Welchem Wellaid 5182 fluid inhibitor.

7-21-92 Lay down tubing, shut well in. Well TA'ed.

THIS APPROVAL EXPIRES AUG 01 1993

14. I hereby certify that the foregoing is true and correct

Signed

W. M. Crook

Title

Prod. Supt.

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

NMOCD

APPROVED

NOV 19 1992

AREA MANAGER