

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Johnson	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Basin Dakota	
Blanco Mesa Verde Ext	
12. County	
Rio Arriba	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
Southland Royalty Company

3. Address of Operator
P.O. Drawer 570, Farmington, New Mexico 87401

4. Location of Well
UNIT LETTER I, 1590' FEET FROM THE south LINE AND 1000 FEET FROM
THE east LINE, SECTION 7 TOWNSHIP 25N RANGE 3W N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
7127' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Spud and Casing Reports</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-01-80 Spudded 12-1/4" surface hole at 1:30 P.M. 11-01-80 and drilled to a total depth of 260'.
Ran 6 joints (241') of 9-5/8", 32.30#, H-40 casing set at 253'.
Cemented with 110 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl₂.
Plug down at 8:00 P.M. 11-01-80.
Cement circulated to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED P. E. Fields TITLE District Engineer DATE November 4, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE NOV 7 1980

CONDITIONS OF APPROVAL, IF ANY: