

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1.

OIL WELL ☐

GAS WELL ☒

OTHER-

2. Name of Operator

Southland Royalty Company

3. Address of Operator

P.O. Drawer 570, Farmington, New Mexico 87401

4. Location of Well

UNIT LETTER I, 1590 FEET FROM THE south LINE AND 1000 FEET FROM

THE east LINE, SECTION 7 TOWNSHIP 25N RANGE 3W NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Johnson

9. Well No.

1

10. Field and Pool, or Wildcat

Basin Dakota

15. Elevation (Show whether DF, RT, GR, etc.)

7127' GR

12. County

Rio Arriba

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Casing Report ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/19/80 Ran 199 joints (8198') of 5-1/2", 17.0# & 15.5#, K-55 casing set at 8191'.  
DV tools at 3757' and 6102'. Cemented as follows:

1st Stage: with 165 sacks of 50/50 Poz with 6% gel and 1/4# gel flake per sack followed with 50 sacks of Class "B" with 1/4# gel flake per sack. Plug down at 11:30 A.M. 11/19/80.  
2nd Stage: with 105 sacks of 50/50 Poz with 6% gel and 1/4# gel flake per sack followed with 50 sacks of Class "B" with 1/4# gel flake per sack. Plug down at 4:00 P.M. 11/19/80.  
3rd Stage: with 270 sacks of 50/50 Poz with 6% gel and 1/4# gel flake per sack followed with 50 sacks of Class "B" with 1/4# gel flake per sack. Plug down at 6:30 P.M. 11/19/80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

R. E. Fitch

TITLE

District Engineer

DATE

November 20, 1980

Original Signed by CHARLES GUNLSON

APPROVED BY

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

NOV 24 1980

CONDITIONS OF APPROVAL, IF ANY: