

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR  
Mobil Producing TX. & N.M. Inc.3. ADDRESS OF OPERATOR Nine Greenway Plaza,  
Suite 2700, Houston, Texas 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790 FSL & 1540 FEL  
AT TOP PROD. INTERVAL: Same as surface  
AT TOTAL DEPTH: Same as surface16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐

## 5. LEASE

Santa Fe 078914

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## 7. UNIT AGREEMENT NAME

## 8. FARM OR LEASE NAME

Lindrith B Unit

## 9. WELL NO.

6

## 10. FIELD OR WILDCAT NAME

Chacon-Dakota Associated

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T24N, R3W

## 12. COUNTY OR PARISH

Rio Arriba

## 13. STATE

New Mexico

## 14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6993' GR

RECEIVED

OCT 16 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-28-80 - Ran PDC 7497-6000. Perf w/1 JSP2F @ 7242-56, 7262-68, 7300-06, 7322-26, 7334-44, 7350-70, (total 36 holes). GIH W/RBP + pkr set @ 7390. Treat perfs 7300-70 w/2000 gal 2% KCl wtr. + 36 BS. Isolate perfs 7242-68. Treat w/2000 gal 2% KCl + 18 BS.

9-29-80 - SWF perfs 7242-7370 w/50,000 gal + 100,000# 20/40 mesh. Ran FEL 7368-7100, good frac thru all perfs. Set RBP @ 7210 perf w/1 JSPF 7124-62, 7170-72.

10-1-80 - Perf w/1 JSPF @ 7144, 76, 78, 80, 82, 84.

10-2-80 - SWF perfs 7124-84 w/50,000 gal + 100,000# 20/40 sd.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Authorized Agent DATE September 30, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY, HERE

OCT 16 1980

\*See Instructions on Reverse Side

BY [Signature]