UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

UNITED STATES	
DEPARTMENT OF THE INTERIOR	5. LEASE SF 081347
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Federal
1. oil gas other	9. WELL NO.
2. NAME OF OPERATOR	2
Reading & Bates Petroleum Co.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	West Lindrith-Gallup Dakota Pool
1125 17th St. Suite 2300 Denver, CO 80202	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 17- T 24N, R 3W
AT SURFACE: 2310' FNL 2300 FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	

15. ELEVATIONS (SHOW DF, KDB, AND WD)

1.	oil well	k	gas well		other				
2.	NAM	E OF C			es Peti	roleur	n Co.		,
3.	ADD			RATOR n St.		2300	Denver,	∞	80202
4.	LOC		OF WE	LL (REF	PORT LOC	ATION	CLEARLY. S	ee sp	ace 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) Production casing

SUBSEQUENT REPORT OF:

(NOTE; Report results of multiple completion or zon change on Form 9-330.)

6842 KB

pertinent da 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give including estimated date of starting any proposed work. If well is directionally drilled, give subsurface local measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran production casing; 236 jts 4 1/2" 11.60 lb/ft K-55 set @ 7582.73 KB. Stage collar @ 3309.16 KB. Cemented 1st stage w/ 475 sx 50-50 poz w/ 2% Gel, 6 1/4#/sk gilsonite & 6 lbs/sk salt. Plug down @ 12:34 a.m. 1-1-81. Cemented second stage w/ 200 sx 65-35 poz w/ 12% Gel, 6 1/4 lbs/sk gilsonite tailed in w/ 50 sks Class "B" neat. Plug down @ 5:40 a.m. 1-1-81.

Subsurface Safety Valve: Manu. and Type		Set @	F t
Subsurface Safety valve, Mariu, and Type			
18. I hereby certify that the foregoing is t	rue and correct		
SIGNED David L. Blosser	TITLE Petroleum	Engineerbate 1-5-81	
	(This space for Federal or St	tate office use)	
metal into a dia di dia metalah	مد أ		
APPROVED BY	TITLE	DATE	
CONDITIONS OF APPROVAL IF ANY			
υβι. Ο Ο 1991	N	IMOCO	
	- •	WUL.	

Military District

-- *See Instructions on Reverse Side