

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
501 Airport Dr., Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1600' FSL x 1780' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

13. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) Completion Operations

5. LEASE Jicarilla Contract 146	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Jicarilla Contract 146	
9. WELL NO. 39	
10. FIELD OR WILDCAT NAME Gonzales Mesaverde/Otero Chacra	
11. SEC., T., R. M., OR BLK. AND SURVEY OR AREA NW/4, SE/4, Section 3, T25N, R5W	
12. COUNTY OR PARISH Rio Arriba	13. STATE New Mexico
14. API NO. 30-039-22522	
15. ELEVATIONS (SHOW DF, KDB, AND VD) 6605' G.L.	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 9-22-81. The total depth of the well is 5407' and the plug back depth is 5253'. Perforated intervals from 5076'-5086', 5105'-5134', 5196'-5200', 5211'-5215, and 5224'-5228' with 2 SPF, a total of 100 .38" holes. Fraced the formation with 40710 gallons of frac fluid, and 49170 pounds of 10-20 sand. Landed 1-1/4" tubing at 3781' and 2-1/16" tubing at 5214'. Released the rig on 10-6-81.



Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Original Signed By E. E. SVOBODA TITLE Dist. Admin. Supvr DATE 10-12-81

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

BY Smn