

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1120' FNL x 1120' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Completion ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

Jicarilla Contract 148

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Contract 148

9. WELL NO.

25

10. FIELD OR WILDCAT NAME

Otero Chacra/South Blanco Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NE/4, NE/4, Section 15,

T25N, R5W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

14. API NO.

30-039-22525

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7002' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 2-21-81. Total depth of the well is 4274', and plug back depth is 4228'. Perforated intervals from 4116-4140 with 2 spf, a total of 48, .38" holes. Fraced with 1796 gallons of foam and 19,000# of 10-20 sand. Fraced Chacra with 57,000 gallons of foam and 222,500# of 10-20 sand. Perforated intervals from 3286-3302, and 3234-3264 with 2 spf, a total of 92, .38" holes. Fraced Pictured Cliffs with 90,000 gallons of foam and 156,000# of 10-20 sand. Landed 2 3/8" tubing at 3304'. Released the rig on 3-1-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed by

SIGNED E. E. SVOBODA

TITLE Dist. Admin. Supvr DATE 3/11/81

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

MAR 17 1981

BY [Signature]
FARMINGTON DISTRICT