

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)

AT SURFACE: 1120' FNL X 1120' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT ON:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR PADIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON

(other) Completion Operations

5. LEASE
Jicarilla Contract 148

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Contract 148

9. WELL NO.

25

10. FIELD OR WILDCAT NAME Otero Chacra/
South Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA NE/4, NE/4, Section 15,
T25N, R5W

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

14. API NO.

30-030-22500

15. ELEVATIONS (SHOW DE, KDB, AND WOB)
7002' C.L.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)

Completion operations commenced again on 8-13-81. Total depth of the well is 4274' and the plugback depth is 4228'. There were no perforations or fracturings during the completion operations. Cleaned out sand to 3400' and drilled out bridge plug at 3400'. Cleaned out rest of sand to 4228' and blew the hole clean with air. Packer was set at 3347'. Landed the 2-1/16" tubing at 4138' and the 1-1/4" tubing at 3304'. Released the rig on 8-18-81.

Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed by

SIGNED E. E. SYOCEA

TITLE Dist. Admin. Supvr. DATE 8-21-81

(This space for Federal or State office use)

APPROVED BY
CONCURRENCE OF APPROVAL, IF ANY.

TITLE

DATE

ACCEPTED FOR RECORD

AUG 26 1981

*See instructions on Reverse Side

FARMINGTON DISTRICT

BY

nmote