## STATE OF NEW MEXICO

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leskage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator MER	IDIAN C	IL INC	Le2se <u>~</u>	TICAF							
Location of Well: Unit	Sec. 34	Twp25N	Rge	5v	J	Coun	ry RI	O ARRIBA			
		TYPE OF PROD. (Oll or Gee)		METHOD OF PROD. (Flow or Art. Lift)		PROD. MEDIUM (Tog. or Cog.)					
Completion CHA	GAS		FLOW			TBG					
Lower Completion	GAS		FLOW			TBG					
		PRE-FLC	W SHUT-IN P	RESSURE	DATA						
Upper 5-3	AYS			•		(Yes or No)					
Lower Completion 5-3-92		Langth of time shu	ength of time shut-in 3 DAYS		SI press. psig		Stabilized? (Yes or No)				
FLOW TEST NO. 1											
Consmenced at (hour, date) # 5-6-92					Zone producing (Upper or Lower)		LOWER				
TIME (hour, date)	LAPSED TIME SINCE#	Upper Completion	Lower Completion	•	PROD. ZONE TEMP.		REMARKS				
5-4		677	56b								
5-5		677	784								
5-6		682	796				E.	146.			
5-7		676	304				11.02				
5-8		676	284			OIL CON DIV					
						436	DIST.				
Production rate d	uring test						,				
Oil:BOPD based onBbls. inHoursGravGOR											
Gas: MCFPD; Tested thru (Orifice or Meter):											
MID-TEST SHUT-IN PRESSURE DATA											
Upper Hour, date shut-in Length of time shut-in			···	Si press. paig			Stabilized	? (Yes or No)			
Completion   Lower   Hour, date shut-in   Length of time   Completion			Si press, peig		ig	Stabilized? (Yes		? (Yes or No)			

FLOW TEST NO. 2

mmenced at thour, da	10) 中丰		Zone producing (Upper or Lower):				
TIME LAPSED TIME		PRESSURE		PROD. ZONE			
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS		
	<del></del>	<del></del>					
	<u> </u>	·	<del> </del>				
			4				
ıs:		мсі	FPD: Tested thru		s Grav GOR er):		
* · · · · · · · · · · · · · · · · · · ·		ion bassin consider		mulata to the be	est of my knowledge.		
•				-			
			19 (	Operator ME	RIDIANOIL		
New Mexico C	Oil Conservation	Division	_		Spring re-sy		
	. Jigraf oy IPAR		I	3 <b>y</b>	Control of the second		
N (198	e Maria de la Maria de Caracteria.	U. M. 1978 DV 197		Title			
					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
cle <u>DEPUTY</u>	OIL & GAS INSP	ector, Dist. #	I	Date			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone testa: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).