

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1660' FSL & 990' FWL (NW SW)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) Mesa Verde Zone

SUBSEQUENT REPORT OF

RECEIVED
JUL 27 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

5. LEASE

Jic. Cont. 10

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME

Jicarilla - Apache

8. FARM OR LEASE NAME

Jicarilla "L"

9. WELL NO.

#7

10. FIELD OR WILDCAT NAME

Pictured Cliffs/Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34 T25N R5W

12. COUNTY OR PARISH

Rio Arriba


13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6751' GR

(NOTE: Report results of multiple completion or change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Test results on the Mesa Verde zone indicate 100% formation water. We respectfully request permission to place 5 sacks Class "B" cement on production packer at 4909' with wireline bailer. Run in hole with cast iron bridge plug, set at 3880'. Place 5 sacks Class "B" cement on top of cast iron bridge plug with wireline bailer, for a 60' fill.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

James F. Sims

Exploration/Development
Superintendent

DATE July 27, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

NMOCC

*See Instructions on Reverse Side

JUL 27 1981
James A. Gillham
for JAMES F. SIMS
DISTRICT OIL & GAS SUPERVISOR