

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Supron Energy Corp. % John H. Hill, et al
3. ADDRESS OF OPERATOR Suite 020, Kysar Building  
300 W. Arrington, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1660' FSL & 990' FWL (NW SW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Mesa Verde Zone

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒



5. LEASE  
Jic. Cont. 10
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A
7. UNIT AGREEMENT NAME  
Jicarilla/Apache
8. FARM OR LEASE NAME  
Jicarilla "L"
9. WELL NO.  
#7
10. FIELD OR WILDCAT NAME  
Pictured Cliffs/Chacra
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 34 T25N R5W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6751' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pulled 148 joints (4795.1') of 2 3/8" tubing. Place 5 sx. Class "B" cement on top of production packer at 4909' with wireline bailer, 60' fill up to 4849'. Set cast iron bridge plug at 3890'. Place 5 sx. Class "B" cement on top of bridge plug with wireline bailer for 60' fill up to 3830'. Job complete at 5:00 P.M., 8/4/81. Tag and test plug after 12 hours, plugs held.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Norman V. Wallis TITLE Exploration/Development Superintendent DATE August 10, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

MMCC

\*See Instructions on Reverse Side

BY Eden