## UNITED STATES

## DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1 oil gar	8. FARM OR LEASE NAME Jicarilla Contract 146
well well other	9. WELL NO.
2. NAME OF OPERATOR Amoco Production Company	35  10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Otero Chacra/Gonzales MV
501 Airport Dr., Farmington, NM 87401  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK AND SURVEY OR AREA SW/4, NW/4, Section 3 T25N, R5W
AT SURFACE: 1570' FNL x 1110' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Rio Arriba New Mexico  14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	— <u>I</u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6602' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0002 GE
FOEL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	randra de la companya de la company Na la companya de la
ABANDON*	<del></del>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertin	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*
Spudded a 12-1/4" hole on 6-18-82 and drill surface casing at 298' on 6-19-82 and cemen cement with 2% CaCl <sub>2</sub> . 17 sx good cement ci a TD of 5345' reached on 6-29-82 and set 5-at 5345' on 6-29-82 and cement in 2 stages.  1. Cement with 360 sx class B cmt. with 65 plug/sx with .8% ELA. Tailed in with 100 stages.  2. Cmt. with 620 sx class B cmt. with 65/3 plug/sx with .8% FLA. Tailed in with 100 stages. Temp log showed cmt. top stages.	ted with 300 sx class "B" neat reulated to surface. Drilled to 1/2" 17# K-55 production casing /35 POZ, 6% gel, 2# medium tuf x class B neat. 5 POZ, 6% gel, 2# medium tuf x class B neat cement. Did not
<b>€</b> \$:	
Released the rig on 6-30-82.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Admin. Sup	vr DATE
(This space for Federal or State	office use)
APPROVED BY TITLE TOTALL CONDITIONS OF APPROVAL, IF ANY:	ASSEPTED FOR RECORD
C	-JUL 1.4 1982

as S

\*See Instructions on Reverse Side

FARMINITON DISTRICT

E. C. - 1 Spir att No. 42-885

Jicarilla Contract 146