

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Fed. N.M. 03010

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

John S. Dashko

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 11, T 24 N - R 7 W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

1.

OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Vista Resources, Inc.

3. ADDRESS OF OPERATOR

800 Rio Grande Blvd. N.W., Suite 10, Albuquerque, NM 87104

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2510' FSL 790' FEL (NESE) Section 11, T 24 N - R 7 W
Rio Arriba County, New Mexico

14. PERMIT NO.

Dec. 9, 1980

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6899' GL

6912' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Setting Surface Csg.

REPAIRING WELL

ALTERING CASING


ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1) Spud 12 1/4" sfc. hole @ 1:45 p.m. 12/13/80

2) Ran 8 5/8", K-55, 24# casing in 12 1/4" hole and set @ 335' KB. Dowell cemented w/100 sx Cl B 50/50 litepoz 6 + 2% D-20 Gel + 6 1/4#/sk D-24 Gilsonite + 2% S-1 CaCl. Slurry wt. - 13.2 ppg, Yield - 1.32 cuft/sk. Water - 5.55 gal/sk. Tailed in w/100 sx Cl B Neat + 2% S-1 CaCl. Slurry wt. 15.6 ppg, Yield - 1.18 cuft/sk, Water - 5.2 gal/sk. Cement circulated. PD at 9:00 p.m. 12/13/80. WOC. Nippled up. Pressure tested casing w/rig pump to 800 psig for 30 min. Held okay.



18. I hereby certify that the foregoing is true and correct

SIGNED

C.D. Gritz
C.D. Gritz

TITLE

Secretary-Treasurer

DATE

12/16/80

(This space for Federal or State official use only.)

APPROVED BY

DEC 23 1980

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON DISTRICT

BY

BW

*See Instructions on Reverse Side