Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

/ /
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31 1001

	BIA	#69
6. If India	n, Allottee or Tribe	Name

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FO	DR PERMIT—" for such proposals	Jicarilla Apache
	T IN TRIPLICATE NAPR - 1 1998	7. If Unit or CA, Agreement Designation N/A
1. Type of Well Oil Well Well Other	- and and other	8. Well Name and No. 100.
2. Name of Operator Elm Ridge Resources, Inc.	(505) 326 7099	Apache 12-E
3. Address and Telephone No. 312 W. LaPlata St., Farmi	naton NM 87401	30-039-22674 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D	Description)	Basin Dakota
Surface: SWSW 1/8-24n-5	w	11. County or Parish, State Rio Arriba, NM
BHL: Same		
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion	New Construction
CE Suosequent Report	Plugging Back Casing Repair	☐ Non-Routine Fracturing ☐ Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state al give subsurface locations and measured and true vertice) 	l pertinent details, and give pertinent dates, including estimated date of starting a al depths for all markers and zones pertinent to this work.)*	my proposed work. If well is directionally drilled
Followed verbal plugging instr	l well on 1-30-97. Plugging supervised by ructions received from BLM's Steve Salzman or	n 12826-96.
Plug #1 (6525'): Set CIBP @ 6 psi.	6525'. Spot 4 sx cmt on top of CIBP. Pressure t	
Plug #2 (4631' - 4531'): Spo	ot 16 sx balanced plug with tubing @ 4631'.	N 05

Plug #3 (2631- 2531'): Spot 16 sx balanced plug with tubing @ 2631'.

Plug #4 (589' - 489'): Spot 16 sx balanced plug with tubing @ 589'.

Plug #5 (50' - surface): Mix and pump 15 sx cement. Circulated good cement to surface.

	cc: BIA, BLM-Albq. (&OCD), BLM	M-SF, Elm (D&F), Tribe	
4. I hereby certify that the foregoing in true and correct Signed Marketine Marketine and correct	Consultant (505) 466-8120	3-23-98	
(This space for Federal or State office (see) Approved by Conditions of approval, if any:	Title Lands and Mineral Resources	Date MAR 27 1998	