Form 3160-5 November 1983) Formerly 9-331)	UNITED STATE PARTMENT OF THE	INTERIOR TELES	il in Thirbicals; instructions on re- ide)	5. LEASE DESIGNATION AND SERIAL WO Jicarilla 70
SUNDRY	BUREAU OF LAND MANA NOTICES AND REP	ORTS ON WEL	LS	6. IF INDIAN, ALLOTTES OR TRIBE NAME
SUNDRY NOTICES AND REI ONTO (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. (Do not use this form for proposals of the proposals				/Jicarilla Apache
OIL X GAS CAS	OTHER	<u> </u>		S. PARM OR LEASE NAME
2. NAME OF OPERATOR				Jicarilla Apache 70
Chace Oil Com	pany Inc.			9. WELL BO.
ADDRESS OF OPERATOR	- ar Albumioraie N	ew Mexico 87108	3	70-10
313 Washington SE, Albuquerque, New Mexico 87108 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*				10. PIBLE AND POOL, OR WILDCAT
See also space 17 below.) At surface				South Lindrith Gallup-Dakota 11. SBC, T. B., M., OR BLK. AND SURVEY OR AREA
Unit 'C' 660 FNL & 1650' FWL				Sec. 34, T24N, R4W
14. PERMIT NO.	15. ELEVATIONS (Sho	w whether DF, ET, GR, etc.)		
14. PREMIT NO.				Rio Arriba N.M.
	Check Appropriate Box To	Indicate Nature of I	Notice, Report, or	Other Data
		marcare i raiore of r	#088D	QUEST REPORT OF:
NOTIC	B OF INTENTION TO:			REPAIRING WELL
TEST WATER SHUT-OFF	PULL OR ALTER CASING		EL SHUT-OFF	ALTERING CASING
PRACTURE TREAT	MULTIPLE COMPLETE	i I	OTING OR ACIDIZING	ABANDONMENT [®]
SHOOT OR ACIDIZE	ABANDON*	<u> </u>		
REPAIR WELL	CHANGE PLANS		Completion of Kecok	its of multiple completion on Well apletion Report and Log form.) ra, including estimated date of starting any ical depths for all markers and sones perti-
_	ure is submitted for a mechanical plugs		•	REARINED
Ol Desamonont W	ing at 6774.5' KB un echanical bridge plu	g set at 4/30	кв.	OK CON DIV.
3) Cement reta 4) 60' cement 145.5 sks (5) Permanent n	iner @ 3810' KB. plug from 3810' KB - 172 cf) Class 'B' sq echanical bridge plu	3870'KB 4.5 rueezed into Ch	sks (5.37 cf) acra formation	inside casing, 3
Proposed pluggi			n of Diaturo (Cliffs formation.
	cf) cement plug cent - 2850' KB cf) cement plug cent			
Set 100' (8.95 2282 - 2382 ! Kl 2555	(continued, p			
·	foregoing is true and correct	TITLE Vice Pres	ident Product	ion October 13, 1987
(This space for Federa	or State office use)			ATTROVED
		TITLE		DATE AND
APPROVED BYCONDITIONS OF APP	BOVAL, IF ANY:			<u> </u>
	_e λ ∟ • s •	e Instructions on Rev	verse Side	TO AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

U.S. Department of Interior Form 3160-5 Page Two

17) Con't.

Set loc' cement plug across 85/6" casing shoe (176-270) Set a 50' (4.5 cf) cement plug at surface. Set a dry hole marker. Fill all pits, recontour location. Reseed location as required.

Plugging operation to begin November, 1987.