## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER TEAKAGE TEST

Jy Ull UC	ompany	Lease	CRober	ts		·		
					inte	Ri <b>o</b> Ar	riba	
		YPE OF PR	YPE OF PROC ME				PROD WED(UM (The or Grey)	
Home			Gas			Tuning		
			<u> </u>			Tubing		
to Gallu						<u> </u>		
				Ą	Stabilized	12 (Yes or 1941)		
poper Hour, date shut-in Langth or time shut-in pertion 10-25-84			1					
Hour, date shutan sength of time shutan			Stabilized? if es or			? (fes or No:		
-84		EL CAN PERCE	RTTS 4	····	<u> </u>		<u></u>	
		FLOW TEST		Upper > Lowert:				
LAPSED TIME SINCE*	PRES	SURE Lower Completion	PHOD. ZONE YEMP	REMARKS				
O Hr.			÷					
24 Hr	624	620	:	Both	Zones	s Shut	In	
48 Hr	650	717	· ·				н	-
72 Hr	668	750					11	
96 Hr	679	170		Upper	S I.	Lower	Flow	24
20 Hr	689	168	·	Upper	S.I.	Lower	Flow	48
ng test								
BOF	D based on	Bbls_s	n Ho-	.(5	Grav _		OR	
	MCF	PD: Tested thro	(Orifice of Me	ter):				. <del></del> .
	MID II.	EST SHUT-IN P	RESSURE DAT	A				
Upper Hour, date shul-in Geograph of time shut propietion		ut in	S) press part	Stabilized? (Yes or N.				
Lower Completion Length of time shut			5: press c*:2	m E		od? (Yes or Ac.	<del></del>	
					av 13	1984		
				OII	COR	1.07	×	
	AME OF RESERVOID  A Vende  to Gallu  B4  B4  B4  B4  B4  B4  B4  B4  B4  B	### PRE-FICE    PRE-FICE   Langth of time shows   84	### AME OF RESERVOIR OR POOL  ### Verde	### OF RESERVOIR OR POOL	New Parison   New Parison	March   Marc	VPR OF RESERVOIR OR POOL	AME OF RESERVOIR OR POOL   CORE OF MAN   METHOD OF PROC   PROC   PROC   CORE OF MAN   The process of the control of the cont

(Continue on reverse ade)

Dis<sup>1</sup>

Commenced at (hour, de	100年本		FLOW TEST			
TIME (now, date)	LAPSED TIME	PRESSURE		Zone producting (Upper or Lower):		
	SINCE **	Upper Completion	Lower Completion	PROD. ZONE TEMP	REMARKS	
· · · · · · · · · · · · · · · · · · ·			_			
		i				
				•	e esemble and an arrangement of the second	
			· · · · · · · · · · · · · · · · · · ·	* * * * * * * * * * * * * * * * * * *		
				1 ************************************		
	.,					
oduction rate du	uing test					
il:	BOPT	) based on				
25.		DESCU OII	===== Bbls. in	Hours.	Grav GOR	
		MCFP	D: Tested thru	(Onfice or Meter):		
emarks: This	test was	conducted	<u>in conjunc</u>	ction with the	deliverability	
shut in tes	st.					
ereby certify that	t the information	herein contained		nplete to the best of my		
proved	NOV	1 O 1. R 1 3				
New Mexico Oil			19 O <sub>I</sub>	Getty 0	il Company	
Origin	nal Signed by CHA	ARLES CHOLDON	Ву	- Jaul D	Beckert	
DEDIT			Tit	dcField Tec	hnician V	
ic DEPU	ET UIL G GAS INS	SPECTOR, DIST. #3	<b>5</b>			

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter a prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been discushed. Tests shall also be taken at any time that communication is no poeted or when requested by the Division.
- At least 72 hours prior to the commendement of any packer leakage test, the operator shall notify the Drizion in writing of the tract time the test is to be commenced. Offser operators shall also be 80 notified.
- 3. The packer leakage can shall commends when both zones of the dual completion are shut-in for pressure stabilization. Both solpes shall reme a shut-in until the well-head pressure in each has shall-listed, provided hobever, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dutal completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No.. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 exce.

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow eriod, at fifteen-minute intervals during the first hour thereof, and a hourly intervals increafter, including one pressure measurement immediately prior to the beginning of each flow period. T-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midwapoint) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable rest data.

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).