

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3360, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840' FNL & 1730' FEL of Sec. 18
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Set Casing

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079600

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--

7. UNIT AGREEMENT NAME
--

8. FARM OR LEASE NAME
C.W. Roberts

9. WELL NO.
6

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde/Ojito Gallup Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

G Section 18-T25N-R3W

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7103' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 7", 23.0# casing (8 3/4" Hole). Set @ 6160'. Cemented first stage with 250 sx. 65/35 Pozmix cement, 135 sx. 50/50 Pozmix cement, + 75 sx. Class "B" Neat cemen
Opened D.V. tool @ 3735'. Cement second stage with 590 sx. 65/35 Pozmix + 50 sx. Class "B" Neat cement. Circulated out chemical wash & no cement.
Reached T.D. of 8150' @ 1:30 P.M. on 7/27/81. Cement top estimated @ 700'.
Ran 4 1/2", 11.6# liner (6 1/4" Hole). Set @ 8150'. Top of liner hanger @ 6005'.
Cemented with 370 sx of 50/50 Pozmix cement. No cement returns.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DeW. B. Bower TITLE Area Superintendent DATE 8-17-81

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE