Form Approved. Budget Bureau No. 42-R1424

## **DEPAR**

1073	,
Dec. 1973 UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 079600
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
debeodio/ie com = 1	
SUNDRY NOTICES AND REPORTS ON WI	ELLS 7. UNIT AGREEMENT NAME
Somethis form for proposals to drill or to deepen or plug back to	a different
On not use this form for proposals to drill or to deepen or plug back to eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas G	C.W. Roberts
well well other	9. WELL NO.
2. NAME OF OPERATOR	3-A 10. FIELD OR WILDCAT NAME
Getty Oil Company	Blanco MesaVerde/Dakota
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Box 3360, Casper, WY 82602	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See	space 17 L Sec. 18-T25N-R3W
below.) AT SURFACE: 1650' FSL & 810' FWL of Sec	2. 18 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
AT TOP PROD. INTERVAL: Same	Rio Arriba New Mexico
AT TOTAL DEPTH: Same	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF	NOTICE,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
AUTOCOLICUT DEDOD	7090 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPOR	
EST WATER SHUT-OFF	ECEIVED / MILES 1951
FRACTURE TREAT  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE	125.561
REPAIR WELL	(NOTE: Report results of multiple completion or zon change on Form 9-330.)
PULL OR ALTER CASING \( \( \)	I OIL WAS STORY
MULTIPLE COMPLETE	- Q 2 Q 元 3 J - Ha 2 2 2 2 2 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ARANDON*	passarat O. C. M.
(other)T.D. and Set Production Casing	
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (0 including estimated date of starting any proposed work. measured and true vertical depths for all markers and zor Reached T.D. of 8135 degrees 7:45 A.M. on</li> </ol>	nes pertinent to this work.)*
Reaction 1.D. of offs	

Reached T.D. Ran production casing as follows:

D.V. Tools Set @ Hole Size Casing Size Wt. #/Ft. Setting Depth 6001' & 3678' 8135' 7 7/8" 5 1/2" 17, 15.5,& 14#

Dowell cemented the 1st stage w/ 150 sx 65/35 POZ + 495 sx 50/50 POZ. Circ. out 15 sx. Cemented 2nd stage  $\overline{w}/$  410 sx 65/35 POZ + 325 sx 50/50 POZ. Circ. out Cemented 3rd stage w/ 825 sx 65/35 POZ + 50 sx Class B Neat. Circ 25 sx to surface.

Subsurface Safety Valve: Manu. and Typ			Set @	
18. I hereby certify that the foregoing is	true and correct TITLE <u>Area Super</u>	intendenbare	7-6-81	
	(This space for Federal or St			
APPROVED BY	TITLE	DATE		

\*See Instructions on Reverse Side

**NMOCC** 

