

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
Getty Oil Company

3. ADDRESS OF OPERATOR  
P.O. Box 3360, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800' FNL, 1820' FWL Section 20  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Spud and Set Surface Casing.</u>	

5. LEASE  
SF 079601

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
--

7. UNIT AGREEMENT NAME  
--

8. FARM OR LEASE NAME  
Lydia Rentz

9. WELL NO.  
#7

10. FIELD OR WILDCAT NAME  
Blanco MesaVerde/Ojito Gallup Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
C Section 20-T25N-R3W

12. COUNTY OR PARISH Rio Arriba 13. STATE New Mexico

14. API NO.  
--

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5222' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded @ 8:00 P.M. on 8/11/81.

Set casing as follows:

Hole Size	Casing Size	Wt. #/Ft.	Depth Set
12 1/4"	9 5/8"	32.3#	293.5'

Cemented with 165 sx. of Class "B" cement w/ 2% CaCl<sub>2</sub> & 1/4 #/sk. celloflake.  
Circulated 5 bbl. cement at surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dev. Banner TITLE Area Superintendent DATE 8/14/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

