

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other

2. NAME OF OPERATOR

Mesa Petroleum Co.

3. ADDRESS OF OPERATOR

1660 Lincoln St., Suite 2800, Denver CO 80264

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 840' FNL, 500' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Production Casing Report

RECEIVED

JUN 22 1965

U. S. GEO. SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to T.D. of 5750'. Ran 140 joints of new 4 1/2" 10.5#/ft K-55 STC production casing to 5725'. Cemented 1st stage with 350 sxs 50/50 Pozmix with 2% gel. Had good circulation. Cemented 2nd stage with 400 sxs 65/35 Pozmix with 6% gel and 6 1/4#/sack Gilsonite, and 100 sxs 50/50 Pozmix containing 2% gel & 6 1/4#/sack Gilsonite. Had good circulation. Cement top of 1st stage at 3157'. Cement top of 2nd stage est. at 700'. Good bond over Qio Alamo.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Randy H. Brown TITLE Regulatory Coord. DATE 6/17/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

ACCEPTED FOR RECORD

JUL 2 1981

•See Instructions on Reverse Side

6.

NMOCC