

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator BANNON ENERGY INCORPORATED
c/o Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

840' FNL & 500' FWL (NW/4 NW/4)
Unit D, Sec. 31, T24N, R7W

5. Lease Designation and Serial No.

NOO-C-14-20-8451

6. If Indian, Allocated or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Blanco Navajo 31#1

9. API Well No.

30 039 22758

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

Rio Arriba County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

1. Run cast iron bridge plug and set @ 5374'.
2. Spot 12 cu. ft. class "B" cement on top of plug. Gallup plug 5240' - 5374'.
3. Spot 14 cu. ft. class "B" cement @ 3561'. Mesa Verde plug 3400' - 3561'.
4. Spot 74 cu. ft. class "B" cement @ 2025'. Pictured Cliffs - Fruitland - Ojo Alamo plug 1200' - 2025'.
5. Spot 33 cu. ft. class "B" cement + 4% gel from 295' - surface. Pump 62 cu. ft. class "B" cement + 4% gel down bradenhead. Max pressure 500 psi. Surface plug 0' - 295'.

Job complete 3/1/95.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Agent

Date 3/2/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

1. 在 1990 年 12 月 31 日以前，
 2. 在 1990 年 12 月 31 日以前，
 3. 在 1990 年 12 月 31 日以前，

040099A

1999

Appendix I