

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3360, Casper, WY 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1610' FNL & 1010' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

## CHANGE ZONES

ABANDON \*

(other) T.D. and Set Casing

(NOTE: Report results of multiple comparisons or zone change on Form 9-530)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Reached T.D. of 8134' @ 9:30 A.M. on 10/4/81.

Ran production casing string as follows:

<u>Hole Size</u>	<u>Casing Size</u>	<u>Wt. #/Ft.</u>	<u>Depth</u>	<u>Cement Information</u>
8 3/4"	7"	23#	6130'	Cemented 1st stage w/ 430 sx. of 50/50 Pozmix cmt. Open D.V. tool @ 3761' and cement 2nd stage w/ 650 sx. of Lite cmt. + 60 sx. of 50/50 w/ 100 sx. Pozmix cmt. Cement top of 50/50 Poz. estimated at 610'. No cmt. circ. 8 Cement Bond Log has beer bbl. to surf. run - wait on compl. unit
6 1/4"	4 1/2" (liner)	7.6 & 10.5#	Liner top @5967', btm. @8134'. Cmt.	

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED DW Brown TITLE Area Superintendent DATE 10/9/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE 10-1-68

CONDITIONS OF APPROVAL, IF ANY:

NMCC

BY