STATE OF NEW MEXICO



LARRY KEHOE SECRETARY

ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE

1000 RIO BRAZOS ROAD AZTEC, NEW MEXICO 87410 (505) 334-6178

July 29, 1982

Petro-Lewis Corporation P. O. Box 2250 Denver CO 80201

Re: Plugging report, Browning Fee 33 #3, N-33-24N-1W

Gentlemen:

The attached Form C-103, Notice of Intention to Plug and Abandon your Browning Fee 33 #3, has been approved with the following conditions:

- All plugs shall be of Class A, B, or C neat cement and may be accelerated by up to 3% CaCl.
- 2. All plugs are to be separated by gel mud of minimum nine pounds per gallon.
- 3. This office must be notified a minimum of 24 hours before plugging operations are commenced.

The subsequent report of plugging cannot be approved until the following requirements have been met:

- 1. All pits have been filled and leveled.
- 2. A steel marker at least 4" in diameter and approximately 4' above ground level has been set in cement. The well name and number, and the well location by unit letter, section, township, and range shall be permanently welded, stamped, or engraved into the metal of the marker.
- 3. The location has been cleared and cleaned.
- 4. The deadman wires have been removed or cut off 4' below ground level.
- 5. All information required by Rule 1105 has been filed.

The subsequent notice of plugging must state that the above work has been done and that the site is ready for inspection.

Yours truly,

Jeff A. Edmister

Geologist II

JAE:gc