

BMG**BENSON-MONTIN-GREER DRILLING CORP.**

November 6, 1997

FAX TO JOHNNY ROBINSON
505-334-6170

Mr. Johnny Robinson
New Mexico Oil Conservation Division
1000 Rio Brazos Road
Aztec, NM 87410

RECEIVED
N. M. O. C. D.
OIL, GAS, DIV.
NOV 8 1997

Dear Mr. Robinson:

In reviewing the records of the New Namer #2, we found that it was completed, not in the Pictured Cliffs, but in the Nacimiento. Accordingly we propose to plug as set out on the attached Sundry Notice. We request verbal approval of this procedure.

Yours truly,

BENSON-MONTIN-GREER DRILLING CORP.

By:


Albert R. Greer, President

ARG/tp

Enclosure

4900 College Boulevard, Farmington, NM 87402

(505) 325-8874 Fax (505) 327-9207

Procedure for Plugging:

To plug and abandon well, record shows Nacimiento perforated at 2351' to 2361' and 2370' to 2375' with TD at 2397.

Set retainer above perfs. (Top perfs 2351')

1. Propose to set cement retainer between 2360' and 2390' (depending on top of tubing above derrick floor). Maximum open hole below retainer 1.3 barrels, will ~~sketch~~ *use* with 2.6 barrels minimum using 15 sacks.
2. Spot cement plug from retainer to 100 feet above top perforation using minimum of 10 sacks cement. (Note: Ojo Alamo and Fruitland formations are 1000 feet below perforations in this well.)
3. *Spot cement from 174 ft. to the surface.
To cover shoe of surface pipe @ 124'.*

Verbal Approval

Johnny Robinson