

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 410' FNL & 670' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report ☒

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
Jicarilla #416
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Medio Canyon
9. WELL NO.
3
10. FIELD OR WILDCAT NAME
West Lindrith Gallup-Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 36, T24N, R4W
12. COUNTY OR PARISH 13. STATE
Rio Arriba New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7228' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-24-81 Ran 16 joints (742') of 4-1/2", 11.6#, K-55 and 172 joints (7008') of 4-1/2", 10.5#, K-55 casing set at 7755'. DV tool at 3568'. Cemented 1st stage with 535 sacks of Class "B" 50/50 Poz with 6% gel & 1/4# flocele per sack, .6% Halad 9, followed by 70 sacks of Class "B" with 2% CaCl₂. Plug down at 10:45 A.M. 10-24-81. Cemented 2nd stage with 270 sacks of Class "B" 50/50 Poz with 6% gel, followed by 50 sacks of Class "B" with 2% CaCl₂. Plug down at 1:15 P.M. 10-24-81.

535
270
50
920

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ether Greyeyes TITLE Drilling Clerk DATE October 26, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: